TOPAFF

Perfect Sewing

1245/1246

Single And Two-needle locktitch Flat Bed Sewing Machines with Unison Feed



sewing of medium-heavy material,e.g.furniture and car upholsterym leather clothing,leather goods,etc.

TOPAFF

- High traction due to unison feed.
- Even feed motion without any ply-shift of individual layers.
- Large vertical rotary hook with 60% more bobbin thread capacity than other standard-sized hooks.
- Automatic hook lubrication.
- Efficient hook protection against thread jamming due to standard built-in overload coupling (M).
- Rugged and durable machine construction.
- The high top feed lift (7 mm) allows trouble-free sewing of thick materials and an easy sewing over cross seams.
- Easy to service.
- Easy loading and unloading - even of bulky material - due to a high fabric clearance of 14 mm.

AVAILABLE AS ADD-ON KIT

1245	6/07 CN	Special part set for seams with particular bulky cross seams stitch length max 6mm,available for machines with thread trimmer-900/56 and for machines without thread trimmer
	-6/07 CNB	Same as-6/07 CN,but stitch length 8mm
	-17/01-650/03 CN	Part set for binding ,without binding,without binder (for machines without P)
	-40/01 CN*5.0	Piping size 5mm,device for the manufacture and simultaneous insertion of piping between two plies if fabric ,device fastened on retractable carrier.
1246	-6/01 CN	Standard part set for plain seaming operations, available for machines without thread trimmer-900/56 Needle gauges:×4.8;×8.0;×10.0;×12.0







TOPAFF

STANDARD SUPPLY PROGRAM	HOOK PROTECTION DEVICE(M)	FOUR-MOTION-DROP-FEED(P)	THREAD TRIMMER-900/56	AUTOMATIC PRESS-FOOT LIFTER/ BACK TACKING SYSTEM-910/97	STITCH LENGTH IN MM	NEEDLE GAUGE IN MM
1245-6/01 CLPMN	●	●			6	
1245-6/01 CLPMN8	●	●			8	
1245-6/01 CLMN8	●				8	
1245-6/01-900/56 CLPMN	●	●	●		6	
1245-6/01-900/56 CLPMN8	●	●	●		8	
*1245-6/01-900/56 -911/97 CLPMN	●	●	●	●	6	
1246-6/01 CL×6.4 PMN	●	●			6	6.4
1246-6/01-900/56 CS×6.4MN	●		●		8	6.4
*1246-6/01-900/56-911/97 CS×6.4PMN	●	●	●	●	6	6.4

Optional:Long arm machine

1245-6/01-750(Clear work space 750*130mm)

1246-6/01-750(Clear work space 750*130mm)

*An air filter/pressure regulator-925/03 is required for the operation off all machines with-911/97

C=for sewing medium-heavy to heavy materials

L=leather

S=fabric

P=four motion drop feed

This maching is equipped with finger-guard ,belt-and take-up lever guards as standard.subject to changes in design ,weight and dimensions.

**Depending on setting on setting of top feed lift ,material and production process.

DEVELOPED IN GERMANY

Stitchtype: 301(lockstitch)

Max Speed: 2800r.p.m

Top feed lift: 7mm

Fabric clearance: Max.14mm

Needle system: 134-35

Needle size: (Nm in1/100mm);110-140

Balance wheel: 80mm eff.dia

Motor power: 0.37or0.55kw,depending on equipment

Clear work space: 270×115mm

Carton dimensions: 77×62×38

1245

Bedplate dimensions: 476×177mm

Net weight:(sewing head)approx.36kg

Gross weight:(sewing head in carton)approx.44kg

1246

Bedplate dimensions:518×117mm

Net weight:(sewing head)approx.38kg

Gross weight:(sewing head in carton)approx.46kg

TOPAFF
Perfect Sewing

地址：西安市高新区丈八二路31号逸翠尚府北区1栋4单元1201室
Add: 4-1201, Block 1, No.31 Zhangba Er Road, Xi 'an, China-710065
Tel : +86-29-68723798 / 68829612 Web: www.eagleco.cn
Fax :+86-29-68723818 E-mail : sale@eagleco.cn